



WOOD GRILLE

Add a natural design element to any space, while creating a harmonious blend of aesthetics and functionality. An excellent choice for ceilings, Wood Grille can also be used on walls or transition seamlessly from ceiling to wall, providing versatility in design applications.



WOOD GRILLE



madridacoustics.com/grille-wood

SPECIFICATIONS*

- No added urea formaldehyde resins
- FSC®-certified options available
- California Air Resources Board (CARB) compliant
- 100% Pre-consumer recycled wood fiber content thirdparty certification
- Environmentally Preferable Product (EPP) Grademark Program CPA 2-06
- Scientific Certification Systems (SCS) Third-party certification 100 percent pre-consumer recycled fiber
- May contribute to LEED Recycled Content Credits MR 4.1 and MR 4.2
- Density: 47 pounds per cubic foot
- Modulus of rupture: 4,500 psi
- Modulus of elasticity: 550,000 psi
- Internal bond: 140 psi
- Hardness: 955 pounds
- Screw holding:
Face: 230 pounds
Edge: 185 pounds
- Linear expansion, maximum average: 0.35 percent
- Thickness swell, 24-hour soak: 6 percent
- Finished with water-based zero VOC Matt 20 finish
- Class A fire rating - veneer on fire-rated MDF
- Over 200 veneer options available
- Excellent sound absorption with acoustical infill panel (NRC 0.85)**

*based upon Madrid's fire-rated MDF core ** Using 2" foam acoustical backer



madridacoustics.com



A CATALYST ACOUSTICS GROUP BRAND